



The *DSP-2060* is a powerful DSP based audio processor, ideally suited for install and live applications, where it combines the functions of a multitude of conventional products in a compact unit.

## Features

- 2 inputs and 6 outputs - native processing runs at 96k resulting in wider bandwidth (over 30kHz).
- Optimized converters - lower noise and optimized distortion figures.
- Extended processing capabilities - 9 full bandwidth parametric bands available on every output, all switchable between PEQ, high and low shelving responses, and high / low pass variable 'Q' filters.
- Crossover filters on each output offer 48dB/Oct. responses. A gentle 6dB/Oct roll-off response is also included.
- Flexible routing matrix available - in addition to standard fixed configurations such as 2 x 3 way (standard configs are still implemented), any output may be fed from any input or sum of inputs. Edit buttons show routing instantly when pressed.
- Program and Clip Limiters - Look-ahead limiters with automatic and manual time constant facilities.
- Delay memory allows for up to 650mS from any input to any output - extra fine delay resolution on outputs for driver alignment, in 30nS (0.1mm) steps!
- Extended memory capacity - user memories extended from 9 to a maximum of 256.
- 2 x 24 character display with new low profile buttons.
- Auto switching power supply works worldwide on all voltages.

**D.A.S. AUDIO, S.A.**  
C/. Islas Baleares, 24  
46988 Fuente del Jarro  
Valencia, SPAIN  
Tel. 96 134 0525  
Tel. Intl. +34 96 134 0860  
Fax 96 134 0607  
Fax Intl. +34 96 134 0607

**D.A.S. AUDIO OF AMERICA, INC.**  
Sunset Palmetto Park  
6816 NW 77th Court.  
Miami, FL. 33166 - U.S.A.  
TOLL FREE: 1-888DAS4USA  
Tel. +1 305 436 0521  
Fax +1 305 436 0528

**D.A.S. AUDIO ASIA PTE. LTD.**  
25 Kaki Bukit Crescent #01-00/02-00  
Kaki Bukit Techpark 1  
Singapore 416256  
Tel. +65 6742 0151  
Fax +65 6742 0157



## Specifications

### Inputs: 2 electronically balanced

Impedance: > 10k ohms.

CMRR : >65dB 50Hz - 10kHz.

MUTE : ON/OFF

### Outputs: 6 electronically balanced

Source Imp: < 60 ohms

Min. Load: 600 ohms

Max. Level: +20dBm into 600 ohms

MUTE : ON/OFF

**Frequency Resp.:** ±½dB 20Hz-20kHz  
-3dB @ 32kHz

**Dyn. Range:** >116dB 20Hz-20kHz unweighted

**Distortion:** < .02%@1kHz,+18dBm

Maximum Delay: 650 ms

Min Step Size: 0.3uS

**Input Gain:** +6dB to -40dB in 0.1dB steps

**Output Gain:** +15dB to -40dB in 0.1dB steps

### Parametric Equalisation

8 per Input / 9 Sections per Output

Filter Gain: +15dB to -30dB in 0.1dB steps

Freq. Range: 19.7Hz - 32kHz, 1/36 octave steps

Filter Q / BW: 0.4 to 128 / 2.5 to 0.008

(Sections switched to shelving response)

Low frequency: 19.2Hz - 1kHz

High frequency: 1kHz - 32kHz

Shelf gains: ±15dB in 0.1dB steps

### High and Lowpass Filters

Filters: 1 of each per output.

Freq. Range HPF: 10Hz - 16kHz

1/36 octave steps.

Freq. Range LPF: 35Hz - 22kHz

1/36 octave steps.

Responses:

1<sup>st</sup> Order 6dB/Oct.

Bessel/Butterworth/Linkwitz-Riley 12-24-48dB/Oct.

Bessel/Butterworth 18dB/Oct.

### Limiters

Program Limiter:

Threshold: +22dBu to -10dBu

Attack time: 0.3 to 90 milliseconds

Release time: 2/4/8/16/32 x Attack time

“D-Max” Limiter:

Attack Time: -60uS

Release Time: Slow/Medium/Fast

**Display:** 2 x 24 Character LCD

**Input meter:** 2 x 4 point, -24dB to digital clip

**Output meter:** 6 x 4 point, -24dB to +4dB into limit

### Connectors

Inputs: 3 pin female XLR

Outputs: 3 pin male XLR

External: 9 pin DEE connector (RS232)

Power: 3 pin IEC

**Power:** 60 to 250V ±15% @ 50/60Hz

**Consumption:** < 30 watts.

**Weight:** 3.3kg. Net (4.7kg. Shipping)

7.26lb. Net (10.34lb. Shipping)

**Size:** 44 x 482 x 300 (mm)

1.75"(1U) x 19" x 11.8"

Due to continuing product improvement the above specifications are subject to change.

**Latency:** 1.5mS (analogue in – analogue out @ 96kHz)

### D.A.S. AUDIO, S.A.

C/. Islas Baleares, 24  
46988 Fuente del Jarro  
Valencia, SPAIN  
Tel. 96 134 0525  
Tel. Intl. +34 96 134 0860  
Fax 96 134 0607  
Fax Intl. +34 96 134 0607

### D.A.S. AUDIO OF AMERICA, INC.

Sunset Palmetto Park  
6816 NW 77th Court.  
Miami, FL. 33166 - U.S.A.  
TOLL FREE: 1-888DAS4USA  
Tel. +1 305 436 0521  
Fax +1 305 436 0528

### D.A.S. AUDIO ASIA PTE. LTD.

25 Kaki Bukit Crescent #01-00/02-00  
Kaki Bukit Techpark 1  
Singapore 416256  
Tel. +65 6742 0151  
Fax +65 6742 0157